5 Shachihata



(P264)

(P271)

(P273)

Safety Data Sheet Xstamper According to OSHA 29 CFR 1910.1200 HCS & Canada WHMIS Revision Date : 15.10.2014 SECTION 1: Product and Company Identification 1.1. Product identifier Product Name : Jiffy Artline Low Corrosion Paint Marker JK-420 Color : (Black) 1.2. Recommended use of the chemical and restrictions on use Colour Recommended use : Marker ink 1.3. Details of the supplier of the safety data sheet Supplier Company Name : Jiffco International Ltd. Address 835 - West 3rd Street North Vancouver, BC V7P 3K7 Canada Telephone 604-980-2685 : 604-980-8549 Fax Contact (e-mail) : sales@jiffco.net Manufacturer Company Name : Shachihata Inc. Address : 4-69, Amazuka-cho, Nishi-ku, Nagoya City, 451-0021, Japan Telephone : +81-52-521-3600 : +81-52-521-3899 Fax Contact (e-mail) : <u>chem-analysis@ngy.shachihata.co.jp</u> 1.4. Emergency telephone number Telephone : 604-657-9822 SECTION 2: Hazard(s) identification **United States (US)** : According to OSHA 29 CFR 1910.1200 HCS 2012

2.1.1 Classification of the substance or mixture	
Flammable liquids, Category 2	H225 : Highly flammable liquid and vapour
Aspiration toxicity, Category 1	H304 : May be fatal if swallowed and enters airways
Skin corrosion / irritation , Category 2	H315 : Causes skin irritation
Specific target organ toxicity - single exposure, Category 3	H336 : May cause drowsiness or dizziness
Hazardous to the aquatic environment, chronic toxicity, Category 2	H411 : Toxic to aquatic life with long lasting effects

2.1.2 Label elements Hazard pictograms

Signal word

Danger :

Hazard statement Highly flammable liquid and vapour • (H225) May be fatal if swallowed and enters airways (H304) Causes skin irritation (H315) May cause drowsiness or dizziness (H336) Toxic to aquatic life with long lasting effects (H411) Precautionary statement [Prevention] Keep away from heat/sparks/open flames/hot surfaces. - No smoking. (P210) Take precautionary measures against static discharge. (P243) Avoid breathing dust/fume/gas/mist/vapours/spray. (P261) Wear protective gloves/protective clothing/eye protection/face protection. (P280)

Wash hands thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Avoid release to the environment.

[ANSI Z400.1/Z129.1-2010][Shachihata Inc.] [Jiffy JK-420_black_a] 2/6

[Response]	
In case of fire : Use dry chemical powder, form or carbon dioxide for extinction.	(P370+P378)
IF SWALLOWED : Immediately call a POISON CENTER or doctor/physician.	(P301+P310)
Get medical advice/attention if you feel unwell. Rinse mouth.	(P301+P314+P330)
IF INHALED : Remove victim to fresh air and keep at rest in a position comfortable	(P304+P340)
for breathing.	
IF IN EYES : Rinse cautiously with water for several minutes.	(P305+P351+P338)
Remove contact lenses, if present and easy to do. Continue rinsing.	
If eye irritation persists : Get medical advice/attention.	(P337+P313)
IF ON SKIN (or hair) : Remove/Take off immediately all contaminated clothing.	(P303+P361+P353)
Rinse skin with water/shower.	
IF ON SKIN : Wash with plenty of soap and water.	(P302+P352)
If skin irritation occurs : Get medical advice/attention.	(P332+P313)
Do NOT induce vomiting.	(P331)
Collect spillage.	(P391)
[Storage]	
Store in a well-ventilated place. Keep container tightly closed.	(P403+P233)
[Disposal]	
Dispose of contents/container to waste in accordance with	(P501)
local/regional/ national/international regulation (to be specified).	
2.1.3 Other hazards	
Under United States Regulations (29 CFR 1910.1200 - Hazard Communication Standard),	
this product is considered hazardous.	

Canada : According to WHMIS

2.2.1 Classification of the substance or mixture

Class B2 : Flammable Liquids


2.2.2 Label elements

2.2.3 Other hazards



In Canada, the product mentioned above is considered hazardous under the Workplace Hazardous Materials Information System (WHMIS)

2.3 Other information



SECTION 3: Composition/information on ingredients

Chemical Name /	Composition	CAS	Classification (OSHA HCS 2012)	
Generic name	weight %	Registry No.	Hazard Class	Hazard statement
Methylcyclohexane	40 ~ 50	108-87-2	Flam.Liq. 2 Asp. Tox. 1 Skin Irrit.2 STOT.SE. 3 Aquatic Chronic 2	H225 H304 H315 H336 H411
Isoparaffinic Hydrocarbon	1 ~ 10	64742-48-9	Flam.Liq. 3 Asp. Tox. 1 Aquatic Chronic 2	H226 H304 H411
Carbon black	1 ~ 10	1333-86-4	none	none
Synthetic resin	40 ~ 50	Confidential	none	none
total	100			

SECTION 4: First-aid measures

4.1. Description of fire IF INHALED	 st aid measures Remove victim to fresh air and keep at rest in a position comfortable for breathing. Consult a doctor if symptoms persist.
IF ON SKIN	: Remove/Take off immediately all contaminated clothing.Wash with soap and water. If skin irritation/rash occurs or feel unwell, consult a doctor for medical advice.
IF IN EYES	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.Continue rinsing. If eye irritation persists, get medical advice/attention.
IF SWALLOWED	: After rinse mouth immediately, give about 250 ml of water or milk and thin in the stomach, and do not vomit forcibly.Moreover, do not give anything from the mouth to the patient when not conscious.Receive the doctor's treatment (stomach pump) promptly.
Note to Physicians :	
All treatments should	d be based on observed signs and symptoms of distress in the patient

All treatments should be based on observed signs and symptoms of distress in the patient. Consideration should be given to the possibility that overexposure to materials other than this product may have occurred.

SECTION 5: Fire-fighting measures

5.1. Extinguishing media	
Suitable extinguishing media	: Dry chemical powder, foam or carbon dioxide
Unsuitable extinguishing media	: Water jet

5.2. Special hazards arising from the substance or mixture

For initial stage extinction, carbon dioxide or dry chemical powder. When a fire extends, fire is extinguished by a large amount of water spray. Do not discharge extinguishing waters into the aquatic environment.

5.3. Advice for firefighters

In the extinction work, an appropriate protective equipment (gloves, glasses, and mask) has to be worn. Because during a fire, hazardous gases may be generated, fire-fighters have to wear self-contained breathing apparatus and other protective equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency proceduresEvacuate personnel to safe area. Shut off all sources of ignition.No Flares, smoking or flame in area. Put on protective equipment. Ensure adequate ventilation.

6.2. Environmental precautions

Do not throw the leakage thing directly into environment

6.3. Methods and material for containment and cleaning up

In case of a small spill, absorb with dry sand, soil, sawdust, cloth, etc.,

then place in a chemical waste containers.

In case of large spills, dike and prevent overflow, cover spills with foam,

then place in a chemical container using non-sparking tools.

SECTION 7: Handling and storage

7.1. Precautions for safe ha	ndling
Advice on safe handling	: Use with adequate ventilation.
	Avoid contact with skin, eyes and clothing.
	Obtain special instructions before use.
	Do not handle until all safety precautions have been read and understood.
	Do not eat, drink or smoke when using this product.
7.2. Conditions for safe stor	age, including any incompatibilities
Requirements for storage	: Keep containers tightly closed and store in a cool and dry place.
areas and containers	Keep away from heat and flame, ignition source and sunlight.

Keep out of the reach of children.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

ACGIH (2013)		
Methylcyclohexane	TWA	400ppm
Carbon black	TWA	3 mg/m ³

[ANSI Z400.1/Z129.1-2010][Shachihata Inc.] [Jiffy JK-420_black_a] 4/6

OSHA PEL		
Methylcyclohexane	TWA	500ppm
Carbon black	TWA	3.5 mg/m ³
Canada Ontario Provincial		
Methylcyclohexane	TWA	400ppm
Carbon black	TWA	3.5 mg/m ³
Canada Quebec Provincial		
Methylcyclohexane	TWA	400ppm
Carbon black	TWA	3.5 mg/m ³

8.2. Exposure controls

Personal protective equipment

Respiratory Protection	: Use with local exhaust ventilation, when in long use.	
	Avoid breathing vapours. Wear mask to prevent organic gas, if necessary.	
Hand Protection	: Avoid contact with hands. Wear safety gloves, if necessary.	
Eye Protection	: Avoid contact with eyes. Wear safety glasses, if necessary.	
Skin Protection	: Avoid skin contact. Wear personal protection apron, boots, if necessary.	
Environmental exposure controls		
General advice	: Prevent product from entering drains.	

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and cl Appearance	hemical properties : black liquid
Odor	: minor solvent odor
рН	: Not applicable
Boiling point	: No data available
Flash point	: 26.6 °F (-3 °C) (closed cup)
Relative Density (at 77 °F , 25 °C)	: 0.8 ~ 1.0 (g/cm ³)
Solubility in Water	: Insoluble

SECTION 10: Stability and reactivity

- 10.1. Reactivity
 - No dangerous reaction known under conditions of normal use.
- 10.2. Possibility of hazardous reactions
- Under normal conditions of storage and use, hazardous reactions will not occur.
- 10.3. Chemical stability
 - The product is stable.
- 10.4. Conditions to Avoid
- High temperature, Direct sunlight, Fire
- 10.5. Incompatible Materials
 - No data available
- 10.6. Hazardous decomposition products
 - CO, CO_2

SECTION 11: Toxicological information

Acute toxicity		: LD/LC50 values that are relevant for classification [Methylcyclohexane]		
	Oral-rat	LD50	>5,000mg/kg	
	Inhalation-rat	LC50	23.3 mg/l/4H	
	Dermal-rabbit	LD50	>2,000mg/kg	
	[Isoparaffinic Hydroca	arbon]		
	Oral-rat	LD50	>5,000mg/kg	
	Inhalation-rat	LC50	>5,000mg/m ³	
	Dermal-rabbit	LD50	>5,000mg/kg	

 [ANSI Z400.1/Z129.1-2010][Shachihata Inc.] [Jiffy JK-420_black_a] 5/6

 Aspiration toxicity
 : Category 1
 May be fatal if swallowed and enters airways.

 Skin corrosion / irritation
 : Category 2
 Causes skin irritation.

 Specific target organ toxicity
 : Category 3
 May cause drowsiness or dizziness.

 single exposure
 : Carbon black has been classified by the IARC as Group 2B.

 Other materials ; Not listed by IARC, ACGIH, OSHA or NTP .

Regarding the carcinogenicity of carbon black, International Agency for Research on Cancer (IARC) has classified as a group 2B. However, ACGIH (American Conference of Governmental Industrial Hygienists), OSHA (Occupational Safety and Health Administration), NTP (National Toxicology Program, USA) in the classification of suspected carcinogenic to humans has not been done. Therefore, we could not classify the carcinogenicity of GHS from that there is no sufficient data.

: No data available

: No data available

SECTION 12: Ecological information

- 12.1. Ecotoxicity
- 12.2. Persistence and degradability
- 12.3. Bioaccumulative potential
- 12.4. Mobility in soil
- 12.5. Other adverse effects
- No data availableNo known significant effects or critical hazards.

: Category 2 Toxic to aquatic life with long lasting effects

- SECTION 13: Disposal considerations
 - 13.1. Waste treatment methods

Disposal must be made according to official regulations.

Comply with all Federal, State, and Local regulations regarding disposal. Do not allow product to reach ground, any water course or sewage system.

SECTION 14: Transport information

	14.1. UN number	DOT, TDG, IMO / IMDG, IATA / ICAO	:	UN1210	
	14.2. UN proper shipping name	DOT, TDG, IMO / IMDG, IATA / ICAO	:	PRINTING INK,flammable	
	14.3. Transport hazard class(es)	DOT, TDG, IMO / IMDG, IATA / ICAO · Class · Label	:	3 (Flammable liquids.) 3	<u>*</u>
	14.4. Packing group	DOT, TDG, IMO / IMDG, IATA / ICAO	:	Π	
	14.5. Environmental hazards	Marine pollutant	:	No	
	14.6. Special precautions for user	EMS Number	:	F-E,S-D	
14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code			:	Not applicable.	

SECTION 15: Regulatory information

< USA Information >					
OSHA STATUS : This product is hazardous under 29 CFR 1910.1200.					
TSCA inventory : All components of this product are listed in the TSCA Inventory.					
TSCA Hazard Communication Program (40 CFR Part 721) (SNUR)	: not Listed				
EPCRA Section 302 Extremely Hazardous Substances (EHS)	: not Listed				
EPCRA Section 313 Toxic Chemicals	: not Listed				
CERCLA Hazardous Substances	: not Listed				
CAA Section 112(r) List of Substances for Accidental Release Prevention	: not Listed				
California Proposition 65	: Carbon black				
< Canada Information >					

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all the information required by the CPR.

Canada inventory : All components of this product are listed in the DSL/NDSL Inventory.

WHMIS Ingredient Disclosure List (SOR/88-64)

(WHMIS : Canadian Workplace Hazardous Material Information System)

: Methylcyclohexane , Carbon black

SECTION 16: Other information, including date of preparation or last revision

Last Revision Date Preparation Date

: 15.10.2014



EU RoHS Directive(2002/95/EC) and ELV Directive(2000/53/EC) This product does not contain lead, mercury, cadmium, hexavalent chromium, polybrominated biphenyls (PBB) or polybrominated diphenylethers (PBDE).

This data sheet may not be enough when evaluating danger or hazard. The above information, which is created from currently available documents, information and data, may be revised when new findings announced. This document has been written on the assumption that when dealing with a large amount of ink on the business case and emergency. When handling as a normal product, please refer to the notes that is described in the produce or packaging. The information contained herein is not intended to provide any kind of warranty other than information, there is no guarantee for the accuracy of the content.